



Fan BD-Blue 130-C6 0-100% 230-1-50/60 6.5A 48500m³/h

Article number: 60-25-4593



Basic data

Montiert	Mounted
Thermal protection contact	Yes
Type	Installation at a wall
Weight	88.4 kg

Rated values

Phases	1 Ph
Nominal frequency [Hz]	50/60 Hz
Control	0-10 V

Classification

IP protection rating	IP65
Certifications	CE
Efficiency rating (ErP)	E15

Dimensions

Width	1380 mm
Height	1380 mm
Total depth	1060 mm
Diameter	1270 mm
Other dimension	1600 mm

Rated values 50 Hz

Elektrische Nennleistung	1.35 kW
--------------------------	---------

**Rated values 50 Hz**

Nominal voltage single-phase	230 V
Voltage tolerance	-10 - 10 %
Nominal current single-phase	6,5 A
Speed	680 U/min
Power factor	0.99
Ambient temperature	-40 - 40 °C
Sound power level Lw	85 dB
Sound pressure level Lp	61 dB

Volumetric flow rate 50 Hz

Characteristic curve – 0 Pa	48500 m ³ /h
Characteristic curve – 10 Pa	46300 m ³ /h
Characteristic curve – 20 Pa	44100 m ³ /h
Characteristic curve – 30 Pa	41600 m ³ /h
Characteristic curve – 40 Pa	39100 m ³ /h
Characteristic curve – 50 Pa	36500 m ³ /h
Characteristic curve – 60 Pa	33500 m ³ /h
Characteristic curve – 70 Pa	30600 m ³ /h
Characteristic curve – 80 Pa	27100 m ³ /h
Characteristic curve – 90 Pa	22300 m ³ /h

Spec. power 50 Hz

Characteristic curve – 0 Pa	28 W/(1000m ³ /h)
Characteristic curve – 10 Pa	30 W/(1000m ³ /h)
Characteristic curve – 20 Pa	32 W/(1000m ³ /h)
Characteristic curve – 30 Pa	35 W/(1000m ³ /h)
Characteristic curve – 40 Pa	37 W/(1000m ³ /h)
Characteristic curve – 50 Pa	40 W/(1000m ³ /h)
Characteristic curve – 60 Pa	43 W/(1000m ³ /h)
Characteristic curve – 70 Pa	47 W/(1000m ³ /h)
Characteristic curve – 80 Pa	52 W/(1000m ³ /h)
Characteristic curve – 90 Pa	62 W/(1000m ³ /h)

Rated values 60 Hz

Elektrische Nennleistung	1.348 kW
Nominal voltage single-phase	230 V
Voltage tolerance	-10 - 10 %
Nominal current single-phase	6,5 A
Speed	680 U/min
Power factor	0.99
Ambient temperature	-40 - 40 °C
Sound power level Lw	85 dB
Sound pressure level Lp	61 dB

Volumetric flow rate 60 Hz

Characteristic curve – 0 Pa	48500 m ³ /h
Characteristic curve – 10 Pa	46300 m ³ /h
Characteristic curve – 20 Pa	44100 m ³ /h
Characteristic curve – 30 Pa	41600 m ³ /h
Characteristic curve – 40 Pa	39100 m ³ /h
Characteristic curve – 50 Pa	36500 m ³ /h
Characteristic curve – 60 Pa	33500 m ³ /h



Volumetric flow rate 60 Hz

Characteristic curve – 70 Pa	30600 m ³ /h
Characteristic curve – 80 Pa	27100 m ³ /h
Characteristic curve – 90 Pa	22300 m ³ /h

Spec. power 60 Hz

Characteristic curve – 0 Pa	28 W/(1000m ³ /h)
Characteristic curve – 10 Pa	30 W/(1000m ³ /h)
Characteristic curve – 20 Pa	32 W/(1000m ³ /h)
Characteristic curve – 30 Pa	35 W/(1000m ³ /h)
Characteristic curve – 40 Pa	37 W/(1000m ³ /h)
Characteristic curve – 50 Pa	40 W/(1000m ³ /h)
Characteristic curve – 60 Pa	43 W/(1000m ³ /h)
Characteristic curve – 70 Pa	47 W/(1000m ³ /h)
Characteristic curve – 80 Pa	52 W/(1000m ³ /h)
Characteristic curve – 90 Pa	62 W/(1000m ³ /h)